

GALVANIZED WIRE

Class I and III wire range from gage 16 to a $\frac{1}{4}$ inch. They come in strapped rolls ranging from 80 to 800 kg. Loose Wire in stand 600 - 800 kg.

Strapped Coil 800 - 1200 kg

The Steel grades used range from 1004 to 1045, depending on the the application or use of the wire as well as the tension resistance required by the customer.



STEEL WIRES COATED WITH ZINC TO PREVENT OXIDATION AND LOSS OF WIRE INTEGRITY DUE TO CORROSION.

CHARACTERÍSTICS

Depending on their application or use, our galvanized wire is manufactured in commercial grade class 1 or 3 and they meet ASTM A641 international standards.

APPLICATIONS AND USES

The wire's bright and clean outside finish, as well as its resistance to uniform tension allow our wires to be used in a wide variety of products in the farming, crafts, commercial, industrial and automotive industries.

GALVANIZED WIRE	GAGE RANGE	PRESENTATION	APPROXIMATE ROLL WEIGHT (KG)
Commercial and highly resistant	from 16 to 1/4	Stand or Roll	from 800 to 1500

www.magnacero.com

ventas@magnacero.com

MATRIZ LEÓN: RESTAURADORES # 102-A COL. CIUDAD INDUSTRIAL ABASTOS, LEÓN, GTO.

01 (477) 194 18 00